



## Description

TV-60MCU-16 is a high performance and large capacity multi-point control unit. It supports standard H.323 protocol, H.264 (high profile) codec and H.239 dual stream, and extensive network communication protocols. It is with full HD 1080P/60 terminal and media processing.

## Features

- \* HD: 1080P/60
- \* Low latency: Less than 200ms
- \* Low bandwidth: Ultra-low bandwidth, 1M for 1080P HD Conference
- \* Max capacity: one machine 120 users

## Communication Protocol

- \* Multimedia Framework Agreement ITU-T H.323, IETF SIP

## Video Features

- \* Support: H.264 (highest: High profile)
- \* Video Resolution Rate: QCIF, CIF, 4CIF, 480P, D1, 720P, 1080P24, 1080P25, 1080P30, 1080P50, 1080P60
- \* Support: mixed -speed, mixed video formats, mixed protocol conference
- \* Static Graphic: XGA, HD720P, 640 x 480, 1280 x 1024, 1080P (1-60 frames), English subtitles
- \* Supports H.239 dual stream digital technology, primary and secondary streams can reach resolution 1080P60
- \* Bandwidth: 1Mbps for 1080p video conference available

## Audio Features

- \* Audio codec: G.711A/U, G.722, G.722.1, G.722.1.C, G.723, iLBC, AAC and so on.
- \* Lip Sync
- \* Multi-channel mixer
- \* Echo Cancellation
- \* Automatic Gain
- \* Noise cancellation

## Network Features

- \* With dual 100M/1000M network interface
- \* Line can be adapted to DDN, ISDN, ATM, SDH, VPN, dedicated satellite, ADSL, etc
- \* Span the router and firewall to ensure system security, support dual-network interface
- \* Supports H.264 SVC, anti network error code, no interruption to the meeting within a 5% packet loss
- \* Voice is with priority, support Qos strategy
- \* Support H235 signaling encryption, AES media stream encryption
- \* Conference access password
- \* Conference control password
- \* Administrator password

## Conference Features

- \* Support multi-screen, multi-screen layouts, up to 16 pictures per screen
- \* Supports split screen automatically
- \* Director conference mode
- \* Chairman conference mode
- \* MCU convene mode
- \* Meeting room mode
- \* Broadcast mode
- \* Free mode
- \* Supports voice activation function
- \* Support breakpoint re-invitation function
- \* Support remote control HD camera, backlight settings

## Maintenance Management

- \* WEB management operation in English & Chinese version
- \* Device management
- \* User management
- \* Conference management
- \* Supports Telnet, ssh remote maintenance
- \* Zone management according to user and region characteristics
- \* Support large-scale terminal membership and management
- \* Software upgrade: local & remote upgrade
- \* IP network diagnosis: PING, packet loss, delay, jitter detection
- \* Status indication of network packet loss
- \* Supports event logging
- \* Support configuration import and export
- \* Restore factory settings
- \* Zoning management According to user and regional characteristics
- \* Support large-scale terminals for membership and management

## Maintenance Management

- \* Dimensions ( LxWxH ): 675mm x 430mm x 88mm
- \* Weight: 25Kg
- \* Electrical specification
- \* Operating voltage: 100VAC ~ 240VAC
- \* Operating frequency: 50Hz ~ 60Hz
- \* Maximum power consumption: less than 500W
- \* Environment Temperature: 10°C ~ 35°C (working condition) -40°C ~ 55°C (non-operating)
- \* Relative Humidity: 10% ~ 80% (working) 0% ~ 95% (non-operating)
- \* Ambient noise: less than 50dBA