



Features

- * The T-8000B remote control with audio input module is connected with T-8000 through universal industrial standard CAT 5 for each eight zone's volume adjustment or remote line and microphone input at a remote and different location from the control center.
- * Two different options: T-8000B of aluminum material in grey color and T-8000BW of ABS material in white color.
- * Each controller provides eight RJ45 ports for the remote control with audio input module.
- * The CAT 5 wiring is not only featured of cost-effective, convenient layout, but also integration of RS 485 communication, audio transmission and DC 24V power supply together.
- * This module family also has simpler functional module of T-8000C and T-8000D.
- * Remote line by dual RCA and mic by XLR inputs with gain controls.
- * Zone LED indicator with up/down buttons.
- * Volume control is provided for overall output level control.
- * DC 24V power supply from controller, low power consumption 5W.
- * Extra DC 24V power supply is needed when communication distance is more than 50 meters.
- * Analog to digital conversion working principle to adjust controller's volume.
- * Metal mounting box is supplied.

Specifications

Model	T-8000BW
Serial Communication Speed	4800bps
Communication Port	RJ45
Communication Protocol	RS485
Serial Communication Distance	Maximums 1Km
MIC Input Sensitivity	5mV/600Ω Phantom Power: +12V
AUX Input Sensitivity	350mV/10KΩ
Audio Output	0dB/600Ω
Frequency Response	50Hz~18KHz (±1dB)
S/N Ratio	MIC Better than 65dB Aux Better than 75dB
THD	Less than 0.1% at 1KHz
Controls	Volume control
PowerSupply	DC 24V
PowerConsumption	5W
Weight	16Kg
Dimensions	146x48x86mm