



TH-0602



TH-0602A

Features

- * Latest digital design.
- * With microphone, speaking button and indicator lamp that can show and control the state of speech.
- * Single projection; With Anti-gas sonic boom and wind shield.
- * With president priority key; the system sound can be prompted to attract attendees' attention; can be set to terminate for permanent or suspend microphone status of all the speakers.
- * The chairman unit can be placed in any position in loop.
- * The chairman unit is unrestricted by the limiting function.
- * With under-wound capacitive microphone pole and speak halo instructions.
- * High sensitivity microphone.
- * The power for the delegate units is supplied by the master controller at 24 safe voltage.
- * T-shaped 8-core line for unit connection.
- * Two groups of 3.5mm stereo sound output socket; can be used as record and earphone connection.
- * Built-in hi-fi speaker; volume control.
- * With automatic video-tracking function.
- * With a microphone unit connecting cable.
- * In accordance with International Electrical Equipment Certification standards (IEC 60914) and the International Safety Standard UL or CE certification.

- * Latest digital design.
- * With microphone, speaking button and indicator lamp that can show and control the state of speech.
- * Single projection; With Anti-gas sonic boom and wind shield.
- * With under-wound capacitive microphone pole and speak halo instructions.
- * High sensitivity microphone.
- * The system power supply for all the delegate units is provided by the main frame at 24 safe voltage.
- * T-shaped 8-core line for unit connection.
- * Two groups of 3.5mm stereo sound output socket; can be used as record and earphone connection.
- * Built-in hi-fi speaker; volume control.
- * With automatic video-tracking function.
- * With a microphone unit connecting cable.
- * In accordance with International Electrical Equipment Certification standards (IEC 60914) and the International Safety Standard UL or CE certification.

Specifications

Model	TH-0602/TH-0602A
Frequency Response	20-20KHz
Sensitivity	-42dB ± 2dB
S/N Ratio	>96dB
THD	0.1% @1KHz
Reference Sound-receiving Distance	50-300mm
Microphone Length	420, 480 or 650mm
Dimension Of The Appearance	127x146x62mm
Net Weight	0.9kg