



## Features

The high performance compressive master controller is designed especially for conference discussion and voting. It meets all the requirements of modern conference that can manage discussion, decision, voting and commenting according system. It is highly integrated and easy to install.

- \* The master controller operates by connecting to the computer; Can connect 64 delegates airman units; with master extension the communication capacity reaches 250 sets.
- \* Achieve functions of conference discussion, multi-voting, with camera tracking host to realize automatically camera tracking.
- \* Main unit sets microphone turn-on quantity and mode to control conference order.
- \* Voice transferred by built-in hi-fi speaker and external earphone jack.
- \* Audio input and output interfaces can connect sound reinforcement equipments and recording equipments. Built 2x50W power.

## Specifications

| Model                | TH-0802M   |
|----------------------|--|
| Max Delegate Mic Qty | ≤250 units   |
| Frequency Response   | 20-20KHz   |
| S/N Ratio            | >96dB  |
| Crosstalk            | >84dB  |
| THD                  | <0.1% @1kHz  |
| Power Supply         | AC 120V or 220V, 50-60Hz   |
| Input                | Balanced Mic input and unbalanced Aux input                            |
| Output               | Unbalanced line output, unbalanced REC output and balanced line output |
| Output Loading       | >1K Ω  |
| Control Port         | RS232 port for PC and RJ45 port for Video Tracking Controller          |
| Effector Connector   | Effector input and output  |
| Speaker Output       | RMS 50 watts stereo output for 4-16 Ω speakers.                        |
| Power Consumption    | 400 watts  |
| Communication Cable  | Dedicated 8 pins cable   |
| Dimension (WxHxD)    | 480x360x85mm   |
| Weight               | 12.7kg   |