



TS-0621



TS-0621A

Description

The TS-0621 (Chairman unit) and TS-0621A (Delegate unit) are two tabletop discussion microphone, which is designed to work with the conference system controller TS-0604M. The microphone unit is built-in a 2W loudspeaker, a monitor earphone output with attenuator. A dual color indicator for direct visual indication of different service: red for speech and green for apply for speech. Attractive ABS patented design of anti-radio frequency technology to ensure superior sound restoration and voice clarity.

Features

- * Discussion conference system use microphone
- * Chairman unit TS-0621 with priority control over control the delegate unit.
- * Chairman unit speech is not limited by discussion speech quantity.
- * Chairman unit could be connected to anywhere of the system.
- * ABS patented design of anti-radio frequency technology for superior sound restoration & voice clarity.
- * Frequency response 20-20,000Hz.
- * Particular high sensitivity microphone design to avoid any low frequency shock.
- * First-level sound restoration and voice clarity gooseneck microphone.
- * Dual color indicator for direct display of different service: red for speech and green for apply speech.
- * Anti-squeal technology, the built-in speaker will be automatically off when microphone is on.
- * Built-in a 2.5W speaker and earphone monitor output & attenuator.
- * All of the microphone units are linked together hand-by-hand by 8 Pins particular cable.
- * With 2 meters aluminium foil and waterline shielded cable of anti-electromagnetic wave interference.
- * Easy microphone ID set up.
- * All of the microphone units are power supplied by the controller by safe DC 24V.

Specifications

Model	TS-0621 & TS-0621A
Description	Chairman discussion unit & delegate discussion unit
Power Supply	DC 24V powered by controller
Connector	8 Pins particular connector
Power Consumption	2.5W
Earphone	input, 9dBu, 8-32
Directivity	cardioid type
Speaker Power	2W
Microphone Type	condenser microphone
S/N Ratio	>90dB
Crosstalk	80dB
Distortion	<0.1%
Frequency Response	20-20KHz
Max SPL	105dB
Sensitivity	-22dB
Dimension (WxHxD)	225x131x48mm
Microphone Length	415, 480 or 650mm
Weight	0.9kg